

ETL-Certified to UL-1776 Standards and to CSA

**Upright, oil fired burner** delivers high efficiency and maintains constant temperature using diesel fuel, kerosene or

home-heating oil

#1 in North America for High-Pressure Cleaning Equipment



### **Electric / Direct or Belt Drive**

**Simple, easy-to-use control panel** includes adjustable thermostat with precision safety controls

**5 HP, 230V, 1PH electric motor (7955S)** comes with thermal overload protection and manual reset



Hotsy-designed Triplex pumps carry a 7-year limited warranty

> **Convenient hose-reel bracket** accepts swivel or stationary reels for ease in hose maneuverability and storage (optional on gas fired models)

> > Rust-proof, removable, non-contaminating polyethylene fuel tank includes fuel gauge in cap

**Pneumatic tires** for easy maneuvering

Model 795SS: 3.5 GPM @ 2000 PSI; Oil fired; 230V, 1PH; Belt Drive Pump

**37-ft. power cord** with safety **Ground Fault Circuit** Interrupter(GFCI breaker)



- 2.8 to 3.5 GPM @ 1500 to 2000 PSI
- Oil Fired, LP or Natural Gas Fired Burners
- 208V or 230V, 1PH

**FEATURES** 

Direct or Belt Drive Pumps



Model 771 (Propane): 2.8 GPM @1500 PSI; 230V, 1PH; Direct Drive Pump. Model 772-Natural Gas (Model left, shown with optional Portagear Kit & Vapor LP Tank)

www.Hotsy.com

Stainless-steel coil skin provides extra durability to withstand the elements (790SS & 795SS)

XXXXX YEAR COIL WARRANTY

**Heater coil** carries a 5-year warranty

**50-ft. length of** / high-pressure hose for ease in cleaning around a large area

Adjustable high pressure detergent injection ensures high-pressure sudsing for better cleaning Oil Fired, LP or Natural Gas Fired

2.8 to 3.5 GPM @ 1500 to 2000 PSI

Hotsy 7-Year Pump Warranty

Direct or Belt Drive

# Designed for tough, industrial cleaning.

SPECIFICATIONS BELT or DIRECT												DRIVE
MODEL	GPM	PSI	НР	VOLT/PH	AMP	FUEL	BTU/HR	PUMP	DRIVE	PORTABILITY	DIMENSIONS	SHIP WT (lbs)
771	2.8	1500	3	230/1	13	LP	280,000	Hotsy Triplex	Direct	Optional	32"Lx27"Wx45.5"H	415
772	2.8	1500	3	230/1	13	NG	338,000	Hotsy Triplex	Direct	N/A	32"Lx27"Wx45.5"H	415
79055	2.8	2000	4TEFC	230/1	20	Oil	289,900	Hotsy Triplex	Belt	Std	37″Lx28″Wx45.5″H	460
79555	3.5	2000	5	230/1	24	Oil	289,900	Hotsy Triplex	Belt	Std	37″Lx28″Wx45.5″H	500
79555-208	3.5	2000	5	208/1	27	Oil	289,900	Hotsy Triplex	Belt	Std	37"Lx28"Wx45.5"H	500

SS=Stainless Steel



### Clean better with Hotsy detergents

Hotsy pressure washers clean best when matched with our specially-formulated Hotsy detergents. Nearly all Hotsy detergent formulations contain

Hotsy's exclusive advanced-formula HCC additives to help prevent scale build-up and fight corrosion in your equipment. All Hotsy detergents are highly concentrated, so a little goes a long way.

## Spend some time with a Hotsy Expert

Hotsy has more than 130 local distributors in North America, all factory-trained to properly evaluate your high-pressure cleaning needs. Over 80% of Hotsy's distributors have been supportion Hotsy systems for more



porting Hotsy systems for more than 20 years.

This seasoned network of local service professionals will ensure you get the safest, most effective and most efficient cleaning solution to your specific cleaning need.

### **OPTIONS for 700 SERIES**

- 8" Natural Gas or LP-Gas-Fired Draft Diverters (Models 771 & 772) prevent backdrafts; keeps cold air out & prevents water from running down vent pipes
- **8" Oil-Fired Draft Dampener** (Models 790SS & 795SS) barometric; prevent backdrafts; keeps cold air out
- Portagear (Model 771-Propane) for easy movement around the shop
- Propane Tank (Model 771-Propane) Vapor LP Tank
- Hose Reel Bracket (Models 771&772) accepts stationary or swivel hose reels

### Hotsy Accessories customize your application for top performance Telescoping wands extend

to 24-ft. to reach high places without scaffolding

High-pressure turbo nozzles for faster cleaning

360° Pivot and non-pivot hose reels keep hose neatly stored and shop areas safe

Rotary surface cleaner attaches to your pressure washer; reduces overspray and zebra striping





P/N 8.914-224.0 Effective 12/10 Specifications & product descriptions to change without notice. ©2010 Hotsy

NOTE: We are constantly improving and updating our products. Consequently, pictures, features & specifications in this brochure may differ slightly from current models. Flow rates & pressure ratings may vary due to variances allowed by manufacturers of our machine components. We attempt to keep our machine performance within  $\pm 5\%$  of listed specifications.

Distributed by: